



DueBi srl

Sistemi per pulizia e igiene nell'Industria Alimentare e nella Zootecnia

Sede legale : via Villani, 2 - 26900 - Lodi
Sede operativa : via Napoli, 6 - 26900 - Lodi
Web : www.2bi.it
e-mail : duebisrl@2bi.it
Tel. : (39) 0371 610210
Fax : (39) 0371 417859



Microlube 20

Code 3720

Description

The doser MICROLUBE 20 has been designed for small belt systems up to about 20 nozzles. The board rated IP65 contains an electronic timer that provides the ON/OFF cycle of the solenoid valve and starts the pump at the same time. The adjustable frequency of the pump makes the unit easily adaptable to the lubrication requirements of any small belt system. The unit also can be used as booster in the most critical points of the conveyor system. On request the complete spraying nozzle kit with s.s. strip (code 3497) is available.

Main features

Water pressure supply	2,5 to 10 bar (static conditions)
Water inlet	F ½
Solution output	quick fitting 8x10 mm.
Capacity	about 20 nozzles
Solution delivery per nozzle	80 cc/1'
Suggested s.s. nozzle	650025
Voltage supply	24 Vac
Electrical input	15 VA max.
Dosing pump 24V	IP65
Pump delivery	5 lt/hour max.
Pump pressure	5 bar max.
Cyclic timer	1 sec. to 10 hours
S.S. box size (mm)	560x330x170 h
Weight on delivery	10 kgs.