



Trolley 1P

Cod. 3071

Description

This special trolley has been designed to carry up two canisters and one equipment, i.e. Uragel Injector, MicroFoam etc..

The trolley (for one equipment), is composed of the following different s.s. frames:

- the vertical one must be connected to the water mains (3 to 8 bar) by the ball valve, to supply water to the equipments. Also one hose holder is installed.
- The horizontal frame must be connected to the compressed air line (5 to 8 bar); the necessary quick couplers (in/out) are already installed. This frame is also equipped with four rotating s.s. wheels with grey antismark rubber.

The frames will be assembled together and properly fixed by the supplied s.s. Bolts.

The standard trolley code. 3071 is provided with one hose holder and can accept one equipment.

On specific request a trolley with two hose holders code 3072, for two equipments, can be supplied.

Main features

Frame	s.s. pipe D. 30 x 1,5 AISI 304
Equipment mounting plate	30 x 50 cm.
Vertical frame:	water connection ball valve 1/2" G water outputs 2 x 3/8" G
Horizontal frame:	air connection quick coupling 3/8" G Air output 1 x quick coupling (hose D. 6x8)
Water / Air inlet pressure	8 bar max
Base for canister (max 2 Pcs)	30 x 30 cm.
Hose holder	1 - max 30 mts hose x 1/2
Lance holder	2
Maximum load	400 kg
Front wheels / Back wheels	rotating antismark grey rubber
Net weight (without equipments)	12 kg
Size	cm. 90 x 40 x 90 (H)